

POND & WATER FEATURE PUMPS LOW VOLTAGE

RPLV SERIES

Economical quiet running, centrifugal pumps in safe, low voltage, with generous 10m cable lengths (except RP550LV) and outdoor transformers. These pumps have numerous applications for aquariums, garden fountains, table and wall fountains and hydroponics. All are saltwater compatible and are fitted with flow control and prefilter foam (except RP550LV)



| CODE | PUMP MODEL                 | PUMP CABLE LENGTH | DRY-MOUNT FLOODED | DIMENSIONS (mm) |       |        | INLET  | OUTLET             | WATTS    | MAX FLOW (L/Hr) | MAX HD (m) |
|------|----------------------------|-------------------|-------------------|-----------------|-------|--------|--------|--------------------|----------|-----------------|------------|
|      |                            |                   |                   | Length          | Width | Height |        |                    |          |                 |            |
| 9604 | RP550LV 12 Volt AC         | 5m                | NO                | 75              | 50    | 70     |        | 8-10-12mm push fit | 10       | 550             | 1.22       |
| 9659 | RP850LV 24 Volt AC         | 10m               | YES               | 120             | 90    | 85     | ½" BSP | ½" BSP             | 19       | 850             | 1.8        |
| 9673 | RP1100LV 24 Volt AC        | 10m               | YES               | 130             | 90    | 105    | ½" BSP | ½" BSP             | 20       | 1100            | 2.0        |
| 9697 | RP1500LV 24 Volt AC        | 10m               | YES               | 130             | 90    | 110    | ½" BSP | ½" BSP             | 20       | 1500            | 2.0        |
| 9727 | RP2400LV 24 Volt AC        | 10m               | YES               | 155             | 100   | 120    | 1" BSP | ½" BSP             | 40       | 2300            | 2.4        |
| 9758 | RP4000LV 24 Volt AC        | 10m               | YES               | 170             | 120   | 150    | 1" BSP | ¾" BSP             | 70       | 4000            | 2.75       |
| 9901 | Low Voltage Extension Lead | 10m               | -                 | -               | -     | -      | -      | -                  | 12V- 24V | -               | -          |

APPLICATIONS

- Water Features
- Garden Ponds
- Indoor Fountains
- Urns and Amphoras
- Table Fountains
- Hydroponics
- Statues

FEATURES

- Proven Performance
- Fresh or Salt Water
- Fully Submersible
- Quiet, Continuous Operation
- Built in Flow Control
- Pumps with 10m cable (except RP550LV - 5m cable)
- Low voltage outdoor transformers with 1.5m cable
- Electrical Safety Approval
- Kit does not include fountain nozzles



| Head (m) | Approximate Flow Rate in Litres per Hour (Without Restriction) |          |            |            |            |             |
|----------|----------------------------------------------------------------|----------|------------|------------|------------|-------------|
| 2.75     |                                                                |          |            |            |            | (0 @ 2.75m) |
| 2.5      |                                                                |          |            |            | (0 @ 2.4m) | 400         |
| 2.25     |                                                                |          |            |            | 300        | 1000        |
| 2.0      |                                                                |          | (0 @ 2.0m) | (0 @ 2.0m) | 600        | 1300        |
| 1.75     |                                                                | (0@1.8m) | 200        | 250        | 850        | 1650        |
| 1.5      |                                                                | 200      | 400        | 500        | 1150       | 2000        |
| 1.25     | (0 @ 1.2m)                                                     | 300      | 650        | 700        | 1350       | 2400        |
| 1.0      | 40                                                             | 475      | 700        | 850        | 1600       | 2700        |
| 0.75     | 170                                                            | 550      | 825        | 1000       | 1750       | 3000        |
| 0.50     | 400                                                            | 675      | 950        | 1200       | 2000       | 3400        |
| 0.25     | 480                                                            | 800      | 1075       | 1350       | 2200       | 3600        |
| 0.0      | 550                                                            | 850      | 1100       | 1500       | 2300       | 4000        |
| MODEL    | RP550LV                                                        | RP850LV  | RP1100LV   | RP1500LV   | RP2400LV   | RP4000LV    |