

TRANSFER PUMP HIGH PRESSURE
RP TRANSFER SERIES



These Premium grade Honda powered pumps are engineered with quality materials to produce an exceptionally reliable pump. Available with either the GX270 or the GX390 genuine Honda engine, with or without roll frame, in recoil and electric start.

APPLICATIONS


- Water harvesting
- Drainage
- Water truck filling

FEATURES & BENEFITS

- Genuine HONDA engine - backed by Honda 3 year universal warranty
 - 2 year warranty on wet-end and roll frame
 - Self-priming to 6 metres with foot valve
 - Available with or without roll frame
 - Engine with oil sensor
 - 3" BSP threaded fitting
 - Wiring harness available as an option for battery connection
- NOTE: Battery and leads not included with Electric Start option
Use a 12 Volt battery with an ampere -hour rating of at least 18Ah

CONSTRUCTION

- Alloy closed vein impeller and diffuser
- 1" keyway shaft



CODE	MODEL	ENGINE HONDA	START	ROLL FRAME	FUEL TANK	SUCTION SIZE	DISCHARGE SIZE	MAX HEAD (M)	MAX FLOW RATE (L/MIN)	PUMP BODY	HORSE POWER CLASS
8911	RP030HP	GX270	Recoil	-	6.1L	3"	3"	72	620	Alloy	9
8928	RP030HP-RF	GX270	Recoil	Yes	6.1L	3"	3"	72	620	Alloy	9
8935	RP030HPE	GX270	Electric	-	6.1L	3"	3"	72	620	Alloy	9
8942	RP030HPE-RF	GX270	Electric	Yes	6.1L	3"	3"	72	620	Alloy	9
8898	RP030AHPE	GX390	Electric	-	6.1L	3"	3"	72	620	Alloy	13
6870	RP030AHPE-RF	GX390	Electric	Yes	6.1L	3"	3"	72	620	Alloy	13